

2025



SOUTH AFRICAN SUGARCANE
RESEARCH INSTITUTE

MECHANISATION REPORT No. 1



South African Sugar Association
170 Flanders Drive, Mount Edgecombe, KwaZulu-Natal
Private Bag X02, Mount Edgecombe, 4300
Telephone: +27-31-508 7400 Facsimile: +27-31-508 7597
Website: www.sasri.org.za

www.sugarg.org.za



MECHANISATION REPORT NO. 1

2025 UPDATE

COSTING MACHINERY SYSTEMS

Graphs which may be used to estimate the total cost of operating individual machines or complete machinery systems have been updated and are attached. Costs include those for interest on investment (9%), depreciation, licences and insurance, fuel (R20,75/litre - includes a rebate of R0/litre), repairs and maintenance, tyres and the operator. These graphs cover:

Agricultural tractors	: Figure 1
Haulage tractors	: Figure 2
Trailers	: Figure 3
Loaders	: Figure 4
Implements	: Figure 5
Attachments	: Figure 6
Road haulage vehicles - trucks	: Figure 7
Transloading cranes	: Figure 8

To use these graphs, a grower must have a reasonably accurate estimate of the number of hours a machine will operate per year. The total distance travelled by trucks (Figure 7) and the total number of tons handled per year by transloading cranes (Figure 8), must also be known.

The cost per hour (or kilometre) is then read off the relevant graph, against the annual use. Once the cost per operating hour is known, the cost per ton or hectare can be calculated.

In the case of a loader or cutter, the hourly cost of the attachment (Figure 6) must be added to that of the tractor (Figure 1) acting as prime mover.

The use of the graphs is illustrated by the following examples:

EXAMPLE 1:

A total area of 20 ha must be disc-harrowed three times per year. The price of the disc harrow chosen for this task is R80000 and a 60 kW FWA tractor is used to pull it. The effective width of cut is 2,0 m. Calculate the cost per hour and the cost per hectare for the harrowing operation.

Rate of work

From Table 1, a speed of 6 km/h and a field efficiency of 80% are chosen, and field conditions are assumed to be reasonably good.

$$\begin{aligned} \text{Total distance travelled/ha} &= \frac{10\,000}{2,0} && (1 \text{ ha} = 10\,000 \text{ m}^2) \\ &= 5\,000 \text{ m/ha} \end{aligned}$$

$$\begin{aligned} \text{Time required/ha} &= \frac{\text{distance}}{\text{speed}} = \frac{5\,000}{6 \times 1\,000} \\ &= 0,83 \text{ h/ha} \end{aligned}$$

$$\begin{aligned} \text{Rate of work} = \frac{\text{time required/ha}}{\text{field efficiency}} &= \frac{0,83}{0,80} \\ &= 1,04 \text{ h/ha} \end{aligned}$$

Annual utilisation

20 ha are worked three times, ie a total of $20 \times 3 = 60$ ha to be disced. Rate of work is 1,04 h/ha, so the annual utilisation of the disc harrow will be $1,04 \times 60 = 62,4$ hours.

It is assumed that the tractor is used for various other tasks, adding up to an annual utilisation of the tractor of 1 000 hours.

Cost of operation

For the disc harrow, read off from Figure 5 from the graph for R80000, and at 62,4 hours per year, that the cost is R173,39/h. For the tractor, from Figure 1, at 1 000 h/year the cost for a FWA 60 kW tractor is R353,82/h. Total cost is thus $R173,39/h + R353,82/h = R527,21/h$.

To disc one hectare once will thus cost $R527,21/h \times 1,04$ (rate of work) = R548,30/ha.

Note that if the disc harrow could be better utilised, say for 40 ha disced three times per year (i.e. 125 h/year), its cost would drop to R95,68/h, and the total cost per hectare would be reduced to R467,48/ha.

Any other field operation can be costed in the same way. Prices must be for current replacement value. Width of cut or swath covered per pass is important, particularly in fertilising or crop spraying operations, and must be determined as accurately as possible.

EXAMPLE 2:

15 000 tons of cane are to be transported per year from the field to a loading zone. Average one-way distance is 1,5 km. Using a 55 kW 2WD tractor and a single stack self-loading trailer working 200 days, 8 hours per day, calculate the number of tractor-trailer units required, and the cost per ton. Average stack size is 5 tons and one conductor is used with the self-loading trailer.

Number of transport units required

Infield tractor-trailer speed is about 15 km/h (Table 2), and to travel to and back from the field will require $\frac{2 \text{ trips} \times 1,5 \text{ km} \times 60 \text{ min/h}}{15 \text{ km/h}} = 12$ minutes.

To load one stack of cane onto a self-loading trailer takes about 5 minutes (Table 2), unloading requires another 5 minutes and allowance must be made for downtime (10%), say another 2.2 minutes. The total cycle time for this operation should thus be: $12 + 5 + 5 + 2.2 = 24.2$ minutes. There are 480 minutes in an eight-hour day, so $\frac{480}{24.2} = 19$ cycles are possible.

The crop is 15 000 tons per year, or 75 tons per day are to be moved. Payload is 5 tons, so 15 cycles will be sufficient. One tractor-trailer unit can do 19, so it will be adequate.

Annual utilisation

The number of operating hours required per year for this operation must be calculated. Each cycle takes 24.2 minutes, but the tractor and trailer is not operating for all of this time. In fact, only the travelling and the loading time should be considered, i.e. $12 + 5 = 17$ minutes per cycle.

This figure is usually increased by 10% to allow for contingencies and the total annual operating hours are then calculated as: 17 minutes operating cycle + 10% = 18.7 minutes; therefore time for 15 cycles/day for 200 days = $\frac{18.7 \times 15 \times 200}{60} = 935$ hours.

Cost of haulage

From Figure 1, a 55 kW 2WD tractor working 935 hours per year will cost R297,06/h. From Figure 3, a single stack, self-loading trailer working 935 hours per year will cost R119,77/h. Total cost is thus R416,83/h, or $R416,83/h \times 935 = R389736$ per year to haul 15 000 tons, i.e. R25,98/ton.

Any other loading or haulage operation, using any machine or series of machines, can be costed similarly. Performance standards must be realistic and if a grower does not have his own standards, those listed in Table 2 could be used as a general guide.

EXAMPLE 3:

15 000 tons of cane are to be loaded from small hand-made bundles with a hi-capacity Bell 125 (3 cylinder) loader into a 6 ton basket trailer for a 1,5 km haul to a loading zone. The trailer is pulled by a 55 kW 2WD tractor. Calculate the number of units required and the cost per ton for this operation.

Loading

Assume overall annual loading rate is 22 t/h (Table 2)

$$\begin{aligned} \text{Annual hours } \frac{15\,000}{22} &= 682 \\ \text{Cost per hour (Fig 4)} &= R470,90 \\ \text{Total annual cost} &= R470,90 \times 682 = R321154 \\ \text{Cost per ton} &= \frac{R321154}{15\,000} = R21,41/\text{ton} \end{aligned}$$

Haulage

$$\begin{aligned} \text{Cycle time: travel @ 15 km/h} &: \frac{2 \times 1,5 \times 60}{15} = 12 \\ \text{loading 6 tons @ 30 t/h} &: \frac{6 \times 60}{30} = 12 \quad (\text{Instantaneous Rate – Table 2}) \\ \text{unloading} &: 5 \\ \text{downtime} &: \underline{2,9} \\ \text{total} &: 31.9 \text{ min} \end{aligned}$$

$$\begin{aligned} \text{Must do } \frac{15\,000}{200} &= 75 \text{ tons per day} \\ \text{Payload} &= 6 \text{ tons} \\ \text{No of trips required} &= \frac{75}{6} = 12,5 \text{ (say 13)} \\ \text{No of trips possible} &= \frac{480}{31.9} = 15 \end{aligned}$$

So one tractor-trailer unit will be sufficient but it will work a full day. The loader will only operate for $\frac{12 \times 13}{60} = 2,6$ h/day, but will be required in the field for the full day.

Operating hours per year

$$\begin{aligned} 12 + 12 &= 24 \text{ minutes per cycle} \\ \text{plus 10\%} &= 26,40 \text{ min} \end{aligned}$$

Total trip cycles to move 15000t at 6 tons per cycle is 2500 at 26.4 minutes per trip = 1 100 h

One can argue that while being loaded, the tractor and trailer only operates intermittently, say 50%

of the time, and a more acceptable operating time per cycle would be:

$$\begin{aligned} 12 + \frac{12}{2} &= 12 + 6 &= & 18 \text{ minutes per cycle} \\ \text{plus } 10\% &&= & 19,8 \text{ min} \\ \text{Time for 2500 cycles/year} &= &= & \frac{19,8 \times 2500}{60} = 825 \text{ h} \\ \text{Tractor cost (Fig 1)} &= &= & \text{R } 312,03/\text{h} \\ \text{Trailer cost (Fig 3)} &= &= & \text{R } 126,73/\text{h} \\ \text{Total cost} &= &= & \text{R}438,76/\text{h} \\ \text{Total annual cost} &= &= & \text{R}438,76/\text{h} \times 825 = \text{R } 361977 \text{ to haul } 15\,000 \text{ tons} \\ \text{Cost per ton} &= &= & \text{R } 24,13/\text{ton} \\ \text{Total system cost} &= &= & \begin{aligned} &\text{loading} &= & \text{R } 21,41/\text{ton} \\ &+\text{hauling} &= & +\text{R } 24,13/\text{ton} \\ &&= & \text{R } 45,54/\text{ton} \end{aligned} \end{aligned}$$

This can be compared with Example 2, where the cost for a similar situation, using self-loading trailers was found to be R25,98/ton, excluding the cost of manual stacking.

Haulage costs could be reduced if a 35 kW 2WD tractor is used. Cost per ton for such a tractor and the 6-ton basket trailer would be R21,12/ton. (Tractor cost = R257,28/h)

Alternative

Use two 55 kW 2WD tractor-trailer units.

Operating hours per year

Each tractor-trailer must now complete 6,5 cycles per day or 1250 cycles per year, each hauling half the allocation, i.e. 7 500 tons per year.

$$\begin{aligned} \text{Operating time (/year)} &= &= & \frac{19,8 \times 1250}{60} = 413 \text{ h} \\ \text{Tractor cost (Fig 1)} &= &= & \text{R}452,06/\text{h} \\ \text{Trailer cost (Fig 3)} &= &= & \begin{aligned} &\text{R } 242,15/\text{h} \\ &= \text{R}694,21/\text{h} \end{aligned} \\ \text{Total annual cost} &= &= & \text{R}694,21 \times 429 = \text{R}286709 \text{ to haul } 7\,500 \text{ tons} \\ \text{Cost per ton} &= &= & \text{R}38,23/\text{ton} \\ \text{Total system cost} &= &= & \begin{aligned} &\text{loading} &= & \text{R } 21,41/\text{ton} \\ &+\text{hauling} &= & +\text{R}38,23/\text{ton} \\ &&= & \text{R}59,64/\text{ton} \end{aligned} \end{aligned}$$

The daily task will, however, be done in 4 hours.

EXAMPLE 4:

15 000 tons of cane per year are to be transported 15 km from a loading zone to a mill. Calculate the cost for transloading by Tractor trailed crane and for haulage. Bundles average 4 tons each.

Transloading

Five minutes are required to unload a bundle from infield trailers and another 5 minutes (Table 2) to load it later onto a truck.

$$\begin{aligned} \text{Annual operating hours} &= \frac{15\,000}{4} \times 10 \text{ min} \\ &= 3\,750 \text{ bundles} \times 10 \text{ min each} \\ &= 625 \text{ h} \\ \text{Cost per operating hour (Fig 8, graph 1)} &= \text{R}710,89/\text{h} \\ \text{Total annual cost} &= \text{R}710,89 \times 625 = \text{R}444\,306 \\ \text{Cost per ton} &= \frac{\text{R}444\,306}{15\,000} = \text{R}29,62/\text{ton} \end{aligned}$$

Haulage

An 8-ton truck can carry two bundles at a time. If bundles average 4 tons each, 3 750 bundles must be hauled per year, i.e. 1 875 trips.

$$\begin{aligned} \text{Each trip is } 15 \times 2 &= 30 \text{ km} \\ \text{Total annual distance} &= 30 \times 1\,875 = 56\,250 \text{ km} \\ \text{Cost per km (Fig 7)} &= \text{R}13,68/\text{km} \\ \text{Cost per year} &= \text{R}13,68 \times 56\,250 = \text{R}769\,500 \\ \text{Cost per ton} &= \text{R}51,30/\text{ton} \end{aligned}$$

A 14-ton truck can carry three bundles. Annual trips will thus amount to 1 250, i.e. 37 500 km will be travelled.

$$\begin{aligned} \text{Cost per km} &= \text{R}22,48/\text{km} \\ \text{Cost per year} &= \text{R}22,48 \times 37\,500 = \text{R}843\,000 \\ \text{Cost per ton} &= \text{R}56,20/\text{ton} \end{aligned}$$

Table 1: Field efficiencies and operating speeds

IMPLEMENT	SPEED (km/h)	EFFICIENCY (%)
Subsoiler	3,0- 8,0	70-90
Plough, m/b, disc or chisel	3,0- 8,0	70-90
Powered rotary tiller	3,0- 8,0	70-90
Harrow, off-set	4,0-10,0	70-90
Harrow, spike-tooth	4,0-10,0	70-90
Rotary cultivator	6,0-12,0	70-90
Cultivator – general	4,0-8,0	70-90
Cultivator - row crop	4,0- 8,0	70-90
Ridger	3,0- 8,0	60-80
Cane Planter	3,0- 8,0	40-50
Fertiliser spreader	4,0- 8,0	60-75
Long box-type spreader	4,0 - 8,0	40-55
Herbicide boom sprayer	4,0- 8,0	40-60
Mower - cutter bar	8,0-11,0	75-85
Mower – rotary	4,0-10,0	75-85
Rake	4,0- 8,0	70-85
Cutters - whole-stick	3,0-10,0	40-75
Harvester – chopper	3,0-10,0	40-75

Table 2: Performance standards for cane handling operations

OPERATION	STANDARD
Cane cutters/harvesters:	
Front mounted cutter	15-30 t/h
Tractor mounted bundle cane harvester	15-40 t/h
Chopper harvester	20-80 t/h
Loaders (infield):	
non-slewing, tractor mounted	8-15 t/h
slewing, tractor-mounted, loading from windrows	20-60 t/h
non-slewing, self-propelled	
a) loading from windrows	20-25 t/h
b) loading from small bundles	20-25 t/h
instantaneous rate	30 t/h
c) carrying cane to parked trailer	10-25 t/h
instantaneous rate	22 t/h
Transloaders (load and unload):	
crane – self-propelled or Scotch type	5 min/bundle
four-pole gantry	10 min/bundle
Self-loading trailers loading from side or rear	5 min/bundle
Tractor speed:	
infield	10-20 km/h
on road	25 km/h
Lorry speeds:	
short hauls	35 km/h
long hauls	45 km/h

FIGURE 1 AGRICULTURAL TRACTORS

MAR 2025




FIGURE 2 HAULAGE TRACTORS

MAR 2025




FIGURE 3 TRAILERS

MAR 2025




FIGURE 4 LOADERS

MAR 2025




FIGURE 5 IMPLEMENTS

MAR 2025




FIGURE 6 ATTACHMENTS

MAR 2025




FIGURE 7 ROAD HAULAGE VEHICLES - TRUCKS

MAR 2025





FIGURE 8 TRANSLOADING CRANES

MAR 2025



ACKNOWLEDGEMENTS:

- Afrit trailers
- Bell Equipment
- Dezzi Equipment
- Dicla Farming Equipment
- Engen Petroleum
- Errol's Tyres
- Falcon Agricultural Equipment
- Firestone and Bridgestone Tyres
- GC Tillage
- Jupidex Agricultural Machinery
- Mascor Tractors and Implements
- Matriarch Equipment
- Mercedes Benz SA– Commercial Vehicles
- Mnani Implements
- Promac Equipment
- Reid's Engineering
- Rogue Agriculture
- Roadhog Trailers
- Roadking Manufacturing Services
- RyAgri Ry Agriculture
- SA Truck Bodies
- SiteFab Engineering
- Staalmeester implements
- Tillmaster Implements
- Transpec Trailers
- UD Trucks
- Unicab Trailers
- AGFACTS
- South African Cane Growers' Association
- Department: Mineral Reserves and Energy
- South African Reserve Bank

Copyright 2025. All copyright and other intellectual property rights subsisting in this work, including without limitation all text, images, graphics and code contained in this work (collectively, the "Contents") are owned by the South African Sugar Association ('the Owner'). Neither this work nor any of its Contents may be shared, modified or copied in whole or part in any form, or be used to create any derivative work without the owner's prior written permission. Whilst every effort has been made to ensure that the information contained in this tool is accurate, the owner makes no representation, warranty or guarantee relating to the use of this work. The use of this work is at your own risk. The entire risk arising out of your use or the performance of this work remains with you, and neither the Owner nor its consultants or staff can be held liable for any loss or damage, whether direct or indirect, caused by any data, information, record or results available on, obtained through or resulting from the use of this work or caused by the reliance on the information contained in this work. The use of proprietary names should not be considered as an endorsement for their use.